

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SISTEVEN, S.L.U.

www.sisteven.es

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	[m³/h]	Flow rate	η_e [%]	Efficiency
EC	Efficiency category	[Pa]	Static pressure or total (depending on EC)	N	Efficiency grade
VSD	Variable Speed Drive	[RPM]	Rotation per minute	[kW]	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
DTM-9/9-4M 3/4 3V	A	Statisch	Frequenzumrichter (VSD) nicht erforderlich	1.00	37.2	44.6	0.672	2476	363	1347
DTM-10/10-4M 3/4 3V	A	Statisch	Frequenzumrichter (VSD) nicht erforderlich	1.00	39.6	46.5	0.808	3137	367	1304
DTM-10/10-6M 1/3 3V	A	Statisch	Frequenzumrichter (VSD) nicht erforderlich	1.00	35.8	45.2	0.333	2282	188	876
DTM-12/12-6M 1 3V	A	Statisch	Frequenzumrichter (VSD) nicht erforderlich	1.00	37.3	44.1	0.847	4007	284	894