

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

SISTEVEN, S.L.U.

www.sisteven.es

c) Typology	g) Nominal flowrate	k) Nominal external pressure	327/2011	r) LWA radiated
d) Type of drive	h) Effective electric power input	l) Internal pressure drop of ventilation components	o1) Max. Internal leakage index	
e) Type of HRS	i) SPPint	m) Internal pressure drop of non-ventilation components	o2) Max. External leakage index	
			p) Energy performance of the filters	

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
			%	m^3/s	kW	$\text{W}/\text{m}^3/\text{s}$	m/s	Pa	Pa	Pa	%	%	%			dBA		
SS-315/H	NRVU / UVU	Variable Drehzahl	Kein/e	0.234	0.158	230	3.00	206			43.3	2.4			Entfällt	Entfällt	58	2018
SS-350/H	NRVU / UVU	Variable Drehzahl	Kein/e	0.327	0.224	230	3.40	224			45.0	2.4			Entfällt	Entfällt	56	2018
SS-400/H	NRVU / UVU	Variable Drehzahl	Kein/e	0.443	0.304	230	3.52	238			46.1	2.4			Entfällt	Entfällt	58	2018