

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SISTEVEN, S.L.U.

www.sisteven.es

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	[m³/h]	Flowrate	η_e [%]	Efficiency
EC	Efficiency category	[Pa]	Static pressure or total (depending on EC)	N	Efficiency grade
VSD	Variable Speed Drive	[RPM]	Rotation per minute	[kw]	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
SLINE-100			Non soumis à ErP. Pe < 125 W							
SLINE-125			Non soumis à ErP. Pe < 125 W							
SLINE-150			Non soumis à ErP. Pe < 125 W							
SLINE-200			Non soumis à ErP. Pe < 125 W							
SLINE-250	A	Statique	L'installation d'un variateur de vitesse n'est pas nécessaire	1.00	32.6	43.4	0.197	899	258	2400
SLINE-315	A	Statique	L'installation d'un variateur de vitesse n'est pas nécessaire	1.00	30.6	40.1	0.314	1033	334	2315